



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 05 APR 2004

WIPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed *AmBrenner*

Dated 24 March 2004

BEST AVAILABLE COPY

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference **NRJ/P34965GB**

2. Patent application number
(The Patent Office will fill in this part)

0306060.5

17 MAR 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Ricardo Consulting Engineers Limited,
Bridge Works, Shoreham-by-Sea,
West Sussex BN43 5FG, England.

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

England.

687228001

4. Title of the invention

A FASTENING DEVICE

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Kilburn & Strode
20 Red Lion Street
London
WC1R 4PJ

Patents ADP number (if you know it)

125001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 6

Claim(s) 2

Abstract

Drawing(s) 1 + 1 *MA*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

N.R. Jennings

Date 17 March
2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr. N.R. Jennings
Tel: 020 7539 4200

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

A FASTENING DEVICE

5 The present invention relates to a fastening device, particularly for fastening metal to metal connections, and more particularly to a device for fastening together two pieces of material in which mating holes are formed, such as two metallic automotive components.

10 For example, an automobile engine has a sump cover that requires fixing securely to the engine block in order to contain oil inside the sump without any leakage. Usually this is achieved by drilling and tapping a large number of bores around the perimeter of an opening in the engine block and drilling corresponding holes through the sump cover. Bolts are inserted through the holes in the cover and through corresponding holes in a gasket and then screwed into each bore. The screwing in of each bolt is hand started and then
15 finished by machine.

Although a secure connection is obtained, there are several problems associated with this practice. A typical sump cover can be fixed to an engine block using 30 or more bolts. It is both time consuming and expensive to drill and tap a hole for each bolt and then to screw each bolt in and have it machine
20 tightened. When the sump requires servicing it is equally difficult to remove the threaded bolts, which over time can become stuck in place.

It is an object of the present invention to alleviate these problems in a simple and effective manner.

25 According to the invention, a fastening device for retention in a hole comprises an elongate shank with a head and a threaded portion in screw threaded engagement with a cylindrical retainer member, in at least part of whose outer surface there is an annular recess, the depth of which increases in the direction towards the head, the recess accommodating an expansible

member whose internal surface engages the surface of the recess and which extends out of the recess.

The fastening device can be used in place of conventional bolts for fastening together metallic automotive components. The shank is threadable into the cylindrical retainer member, the outer surface of which is not tapped but includes a tapered recess. The expansible member is fitted in the recess and the device is then inserted with a certain amount of force through a hole in one component into a bore in the other component. When the force is removed, the shank will move a certain distance in the direction out of the bore, e.g. as one or other component or a gasket interposed between them expands slightly, and this movement of the shank will cause the tapering surface of the base of the recess in its outer surface to engage the expansible member and cause it to expand into locking contact with the wall of the bore, thereby locking the two components together.

An advantage of the fastening device is that the retainer member slides into the bore. Thus each bore can be plainly drilled and does not require tapping. This is both a cost saving and a labour saving over conventional threaded bolts. The fastening device is easily installed and locked in position, since no rotation is necessary.

Optional features of the invention are set out in the dependent claims. A spring preferably engages the shank in the vicinity of the head and is adapted to engage the margin of the hole and urge the shank in the direction out of the hole. The shank requires loading in order to lock the fastening device into place, and the spring can therefore be used to ensure that the load urging the shank in the direction out of the bore is sufficient if the resilience provided by the cover and gasket, where present, is not sufficient.

The expansible member of the fastening device is preferably a metallic ring, preferably in the form of a split ring. Metal, such as spring steel, is resilient enough when formed as a split ring for the ring to be resiliently

expandable, yet it also is very tough. Thus, the ring is able to dig into the sides of the bore for locking the fastening device into place and remaining locked over long periods of time.

5 The surface of the recess is preferably frustoconical and the internal surface of the ring may also be frustoconical and complementary to the recess surface. This is preferred as the ring can tighten against the tapered surface of the cylindrical retainer recess whilst being maintained in a symmetrical position with respect to the axis of the shank as the shank is unloaded after insertion into the bore. The angles of inclination of the ring internal surface and of the recess tapered surface preferably complement each other so that a close fit can be ensured between the two components. The external surface of the ring preferably has a sharp outer edge at the end of the ring directed toward the shank head. Thus as the ring expands around the widening taper upon unloading of the shank, the outermost edge of the ring external surface digs
10 into the bore surface for locking engagement therewith.
15

The shank may comprise longitudinally spaced ribs for engagement with the margin of a hole in the spring. The ribs enable the spring to engage the shank for urging the shank out of the bore.

20 The fastening device is preferably used for fastening together two metallic automobile components such as a sump and a sump cover. Significant savings can be made in using the fastening device for such an application that requires many such fastenings.

25 The present invention will now be explained in more detail by the following non-limiting description of a preferred embodiment and with reference to the accompanying drawing in which:-

Fig.1 is a schematic cross-section of a fastening device according to the invention when in situ fastening a sump cover to an engine block.

Fig.1 shows a fastening device 1 comprising a shank 2 inside a bore 3 in an engine block 5. The shank 2 comprises an elongate member having a head

portion 10 at one end thereof, a ribbed portion 12 adjacent to the head portion, a necked portion 14 and a threaded portion 16 extending away from the head portion 10. The head portion 10 includes a handgrip 18 for use in installing the shank 2 in the bore 3.

5 The fastening device 1 also comprises a cylindrical retainer member 20 that is of a length that may be slightly shorter than the threaded portion 16 of the shank 2. The cylindrical retainer member 20 has a diameter that is substantially the same as that of the bore 3 into which it is to be installed such that the cylindrical retainer member 20 fits closely inside the bore.

10 The cylindrical retainer member 20 is of a generally annular cross-section. At least part of the inner surface of the retainer member 20 is in threaded engagement with the threaded portion 16 of shank 2. The outer surface of retainer member 20 includes a tapered recess 24 that extends over at least part of its length. The tapered recess has a depth that increases towards
15 the end of the retainer member 20 that is closest to the head 10 of shank 2.

 The fastening device further comprises an expansible split ring 30. The expansible ring 30 preferably has a regular trapezoidal cross-section such that its side surfaces are inclined away from each other at the upper surface of the ring 30 as shown in Fig.1. The ring 30 has a gap (not shown) at one point in its
20 circumference so that the size of the ring 30 may be expanded by moving its two free ends apart. The expansible ring 30 is thus preferably manufactured from spring steel such that the ring 30 has the desired properties of toughness and flexibility whilst being hard-wearing. However, any other suitable material could be used. The upper outer edge of the ring is defined by two
25 surfaces which extend at less than 90°, preferably about 70°, to each other and is thus relatively "sharp" and thus capable of deforming, that is to say digging into, the surface of the bore.

 The fastening device also includes a spring 40. In this embodiment of the invention, the spring is of a plate spring type and has a central aperture in

which the ribbed portion of the shank 12 is received. The spring 40 has a thin elongate cross-section that is bent upwards at the inner 42 and outer edges of the cross-section as shown in Fig.1. The centre portion 44 of the ring cross-section remains flat. The thickness of the spring 40 is just sufficient to enable the inner edge 42 to engage between two ribs of the ribbed portion 12 of shank 2.

The fastening device 1 is shown fastening a metal sump cover 7 to an engine block 5, with the interposition of a sealing gasket 9. The bore 3 in the vessel 5 is a plain bore and requires no tapping. The cover 5 and gasket 9 contain holes that correspond to each of the bores 3.

The fastening device 1 is used by first threading the cylindrical retainer member 20 over the threaded shank portion 16 of the shank 2. The ring 30 is fitted around the retainer member 20, so that it sits in the tapered recess 24. The inclined inner surface of the ring 30 engages to the surface of tapered recess 24 towards the upper end of the recess. Cover 7 and gasket 9 are placed over the bore 3 so that the holes in the components are aligned. Spring 40 is fitted over the ribbed portion of shank 2 so that its inner portion 42 engages between two ribs thereof. The shank 2, with retainer member 20 and ring 30 are then forcibly inserted through the holes in the cover 7 and gasket 9 and into the bore 3. The force of insertion of the fastening device 1 loads the device in direction 'A' as shown in Fig. 1. When the fastening device is fully inserted into bore 3, the flat portion 44 of spring 40 rests on top of the cover 7 and the spring is deformed and urges the shank in the direction out of the hole. A rib 13 of the ribbed portion 12 of shank 2 bears against the spring 40. The handgrip 18 is then released.

The spring 40 provides a resilient force against the compressive force in direction 'A' on the shank 2 such that when the user releases the load on hand grip 18, the fastening device 1 is moved a small distance out of the bore 3 in direction 'B', as shown in Fig.1. This causes cylindrical retainer member 20 to

move vertically upwards, its tapered recess 24 mating against the inner surface of ring 30 and forcing the ring 30 to expand. Consequently, as the gap between cylindrical retainer member 20 and the bore 3 decreases, the outer surface of ring 30 digs into the surface of the bore 3, thereby preventing further outward movement of the shank and locking the fastening device 1 in place.

In certain applications of the fastening device 1, the cover 7 and gasket 9 provide enough resilience against the load applied to shank 2 in direction 'A' to bias the fastening device 1 out of the bore 3 sufficiently without the need for spring 40 to be used. In this case, a metallic plate having a suitable aperture (not shown) replaces the spring 40 to provide a surface against which the ribs 13 of the ribbed portion 12 can locate. Alternatively, the head 10 is enlarged so that it will engage the margin of the hole, in which event the fastening device will resemble a conventional bolt. In use, the bolt is simply inserted into the hole and rotated, e.g. by one turn, and this is sufficient to lock it in position.

The fastening device 1 is removable in a conventional manner by unscrewing the shank 2 out of the retainer 20. In this event, the retainer and ring may be loose in the hole and may be removed separately for re-use or they may remain fixed in position by virtue of the fact that the ring has deformed the wall of the bore, in which case it may simply be re-used when the shank is re-inserted.

Various modifications may be made to the embodiment described without departing from the scope of the invention as defined by the following claims.

CLAIMS

1. A fastening device for retention in a hole comprising an elongate shank
5 with a head and a threaded portion in screw threaded engagement with a
cylindrical retainer member, in at least part of whose outer surface there is an
annular recess, the depth of which increases in the direction towards the head,
the recess accommodating an expansible member whose internal surface
engages the surface of the recess and which extends out of the recess.
10
2. A fastening device as claimed in claim 1 having a spring engaging the
shank in the vicinity of the head that is adapted to engage the margin of the
hole and urge the shank in the direction out of the hole.
- 15 3. A fastening device as claimed in claim 1 or claim 2 in which the
expansible member is a metallic ring.
4. A fastening device as claimed in claim 3 in which the ring comprises a
split ring.
20
5. A fastening device as claimed in any preceding claim in which the
surface of the recess is frustoconical.
6. A fastening device as claimed in claim 3 in which the internal surface of
25 the ring is frustoconical and complementary to the surface of the recess.
7. A fastening device as claimed in claim 3 in which the outer edge of the
ring at the end directed toward the head is defined by two surfaces which
extend at less than 90° to each other.

8. A fastening device as claimed in claim 2 in which the shank comprises longitudinally spaced ribs for engagement with the margin of a hole in the spring.

5

9. A fastening device as claimed in claims 2 to 8 in situ in a hole, the spring urging the shank out of the hole.

10. A fastening device as claimed in any preceding claim in situ fastening
10 together two metallic components of an automotive engine.






Fig. 1

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.